

SERIE U-COMFORT.

Energy-efficient. Low-noise.

new



EXTRA FLAT DESIGN



VERY SILENT



HIGHT ENERGY EFFICIENCY




BACKDRAUGHT SHUTTER INCLUDED

- Simple and compact installation with Recessed Slim Design.
- High Performance plastic Housing design and Helico-Centrifugal Impeller.
- Very Low Noise Level
- Fitted with Low Consumption Motor class B and thermal cut out, ambient temperature max. 40°C
- Rated Voltage 220-240V 50/60Hz (110-127V 60Hz on request).
- Timer and Timer-Hygro models available
- Lots of possibilities to personalize the fan using Accessories to complete the High COMFORT Experience.
- Different Frontal cover designs
- Upgrades through Electronics Systems
- IP-44 and Double Insulation
- Basic Back draught Shutter (included)



CODE	MODEL	COLOR	EAN CODE	VERSION	Ø (mm)	Voltage (V)	SPEED (r.p.m)	Input Power (W)	Maximum Airflow (m³/h)	Sound Pressure Level dB(A)	Weight (Kg)	Units per box
HYGRO SERIES												
01200200	UC-10 HYGRO	□	8422248079860	●●●	100	230	2200	8	110	26	0,65	10
01201200	UC-10 HYGRO SILVER	■	8422248082594	●●●	100	230	2200	8	110	26	0,65	10
01202200	UC-10 HYGRO BLACK	■	8422248082624	●●●	100	230	2200	8	110	26	0,65	10
TIMER SERIES												
01200100	UC-10 TIMER	□	8422248079853	●	100	230	2200	8	110	26	0,65	10
01201000	UC-10 TIMER SILVER	■	8422248082587	●	100	230	2200	8	110	26	0,65	10
01202100	UC-10 TIMER BLACK	■	8422248082617	●	100	230	2200	8	110	26	0,65	10
STANDARD SERIES												
01200000	UC-10 STD	□	8422248079846	●	100	230	2200	8	110	26	0,65	10
01255000	UC-10 STD SILVER	■	8422248082570	●	100	230	2200	8	110	26	0,65	10
01256000	UC-10 STD BLACK	■	8422248082600	●	100	230	2200	8	110	26	0,65	10

DIMENSIONS mm



	Ø A	B	C	D
UC-10	98	150	77,5	18,5



STANDARD In combination with light, fans switches on.



TIMER Electronic timer adjustable from 1 to 20 minutes.



HYGRO Adjustable humidity detector from 30% to 80%, and adjustable electronic timer from 1 to 20 minutes.



SPEED REGULATION Speed adjustable from 1000 to 2200 RPM.

